



ACH3

High Resolution Counting Scale



ACH3

High Resolution Counting Scale

Feature:

- ACH3 up to 1/30,000 display resolution (Internal resolution 1/600,000)
- High speed 24bits AD; Display reading speed faster
- Faster weighing stability
- Faster zero return
- Zero key and Tare key react faster
- LCD displays full tare (Weight-6digits、Unit Weight-6 digits、Quantity-6 digits)
- Auto calibration function, OL protection
- Weight and quantity over-limit warning
- Auto average unit weight, pre-tare function
- Kilogram(kg), pound(lb) weighing modes
- Stable sampling range setting function
- Low power and charging status indication
- Built-in rechargeable battery
- Easily adjusted leveling feet for stability of the scale
- 10 preset unit weight function



Option:

- RS232: Bio-direction transmission, easy data reading or printing
- RS232: FREE FORM CARD (include Real Time Clock)
- 1/30,000(with temperature compensation)display resolution available, more accurate and stable

Specifications:

Model	Capacity	Division	Resolution
ACH 3 - 1.5	1.5 kg (3 lb)	0.1 g (0.0002 lb)	1/15 000
ACH 3 - 3	3 kg (6 lb)	0.2 g (0.0005 lb)	1/15 000
ACH 3 - 6	6 kg (12 lb)	0.1 g (0.0002 lb)	1/30 000
ACH 3 - 7.5	7.5 kg (15 lb)	0.2 g (0.0005 lb)	1/30 000
ACH 3 - 15	15 kg (30 lb)	0.5 g (0.001 lb)	1/15 000
ACH 3 - 15	15 kg (30 lb)	0.5 g (0.001 lb)	1/30 000
ACH 3 - 30	30 kg (60 lb)	2 g (0.005 lb)	1/15 000
ACH 3 - 30	30 kg (60 lb)	1 g (0.002 lb)	1/30 000

Operating Temperature: 0°C ~ 40°C (32°F ~ 104°F); **Approval Model:** -10°C ~ 40°C (14°F ~ 104°F)

Power Supply: AC 110V/220V (±10%) + DC 6V/4AH rechargeable battery

Dimension: 340 × 115 × 310 mm (W × H × D)

Platter Size: 290 × 245 mm (W × D)

Display: LCD, 6, 6 Digits, Height 14 mm, LED Backlight