




Features

- Audible alarm for checkweighing
- Programmable auto power-off to conserve battery usage
- Overload protection to safeguard internal components
- Durable ABS construction suitable for industrial environments
- Sealed keypad to prevent dirt and liquid damage
- Adjustable leveling feet
- Supports connection to a tri-color alarm light.
- Optional RS-232 port for data transfer and connectivity.
- Optional Printer: LP201-US, TP-205, DMP-207

General Specifications

- Units : kg, g
- Display : Red LED Display
- Power Supply : DC 12V 500mA adapter
- Operating Temperature : 0°C to +40°C

Dimensions



Print Format

Format 1

05/03/2024 14:25:44
Serial : 0062
Gross : 1.500 kg
Tare : 0.500 kg
Net : 1.000 kg

Format 2

Date : 05/03/2024
Time : 14:24:43
Serial : 0059
Gross : 1.500 kg
Tare : 0.500 kg
Net : 1.000 kg

Product Details

Model	Capacity	Readability	Platform (mm)	Weight (kg)	L x W x H (mm)
MACS-303	3 kg	0.1 g	260 x 218	4.2	315 x 264 x 110
MACS-306	6 kg	0.2 g	260 x 218	4.2	315 x 264 x 110
MACS-315	15 kg	0.5 g	260 x 218	4.2	315 x 264 x 110
MACS-330	30 kg	1 g	260 x 218	4.2	315 x 264 x 110